




## DOBEL® ANTIPHON

Design and Function at its best



**DESCRIPTION**

**DOBEL®** Antiphon is a laminated sheet metal with decorative foil on one or both sides. It has superior structure-borne sound damping properties and can be used for a wide range of applications. The material has a sandwich construction and is currently primarily used in the automotive and offshore industries, as well as in other industrial and customer products like doors and various types of machinery.

The principle behind **DOBEL®** Antiphon is as simple as it is ingenious, consisting of two metal sheets that enclose a viscoelastic polymeric inner layer. The inner layer and sheet metal quality is chosen on the basis of the requirements regarding acoustics, workability and strength for the application in question. **DOBEL®** Antiphon provides superior sound damping effects in relation to volume and weight and is ideal for use in situations where stringent demands are placed on both design and function.


**THE CHALLENGE**

Acoustics and the reduction of unwanted sound is often one of the most challenging aspects of building interiors for public areas, vehicles, ships, trains, etc. On many occasions there is only limited space available, and the challenge is to achieve highly effective sound damping and soundproofing characteristics without having to use bulky, space-consuming materials and solutions.

**THE SOLUTION**

Modern technology makes it possible to minimise the occurrence of unwanted sound, and powerful tools are now available for the measurement and analysis of sounds and vibrations in order to be able to dampen sound sources and predict the effects of sound reduction measures.

**DOBEL®** Antiphon is a laminated sheet metal with a wide range of foils from which to choose. This makes it possible to use the material for design purposes in relation to visible



surfaces where sound damping is desirable and where stringent demands are placed on visual expression and function. The product is available with both galvanised sheet metal and aluminium as the base material. It can be delivered with various types of inner layer in order to provide different properties in response to different needs.

**DOBEL®** Antiphon is in most respects processed and treated as normal homogeneous sheet metal. With the right tools and techniques it can be bent, shaped, trimmed and cut to suit a variety of areas of use.

**TRY US**

Contact us for further information or for a trial order to see for yourself.



Product	Thickness	Max Width	Length	Weight
<b>Cut Sheet</b>				
<b>DOBEL®</b> Antiphon	0.5 - 1.5 mm/steel layer	Max 1,250 mm	Max 3,000 mm	Max 2 T/Package



**Metalcolour A/S**  
 Agrovej 6  
 DK-4800 Nykøbing F.  
 Phone: +45 5484 9070  
 info@metalcolour.com

**Metalcolour Sverige AB**  
 Emaljervägen 7  
 SE-372 30 Ronneby  
 Phone: +46 457 781 00  
 info@metalcolour.com

**Metalcolour Asia Pte Ltd**  
 17 Tuas Avenue 4  
 SG-639368 Singapore  
 Phone: +65 6898 2535  
 info@metalcolour.com