



# DOBEL® FILM LAMINATED METAL

Safety First

EN 45545 HL3 APPROVED



**DESCRIPTION**

Film laminated aluminium – decorative interior material in a lasting durable and lightweight design. The combination of metal properties, in terms of strength and shapability, **DOBEL® F105** gives a versatile interior material with outstanding economical benefits.

**THE CHALLENGE**

Laminated sheet metal is used in a lot of applications in our daily lives. Wall panels and ceilings in buildings, ships and trains are some structural applications for which the **DOBEL®** material is being used.

Design feature No 1 for these applications is guaranteeing the safety of human lives. This is done by choosing material which has certified ability to reduce spreading of fire and structural strength to withstand physical impact.

Common for all applications is that durability and surface design in colour and structure as well as shape ability are crucial factors for the success and perceived value of the end product.

Wear and tear is the key factor when choosing laminated metal as component material. In the production stage, the metal will be handled, bent and cut into its final shape and form. A process that requires material and surfaces to cope with high degree of mechanical wear and tear.

Once products and surfaces are put into use by end users, surfaces needs to maintain their appearances for many years while exposed to the environment (UV light and temperature), mechanical wear from use and often aggressive cleaning detergents when cleaning the surfaces.

**METALCOLOUR SOLUTIONS AND ADVANTAGES**

“Safety First” – is highest priority and therefore the **DOBEL® F105** series of material is tested and certified according to the highest standards in fire safety. Not only in fire safety is Metalcolour through the **DOBEL®** brand continually pushing the standard to higher levels. By introducing the heat applied non stick protective foil the Metalcolour laminated surfaces are securely protected from damages during



production and handling. Once the end product is finalized the protective foil can be removed easily leaving the surface clean, ready to use with no glue residues on the surface.

Given the extremely high expectancy for wear and tear resistance, the printed **DOBEL®** products by Metalcolour are all supplied with an added anti scratch and chemical detergent resistant protection layer.

Metalcolour has developed a unique lamination process which makes it possible to control the lamination process in a new and innovative way. This innovation makes it possible to broaden the number of materials we can laminate to metal, but as importantly gloss and colour can be controlled to very narrow tolerances.

Metalcolour is as market leading supplier the only company to offer a specific and committed Quality and Service Guarantee.

**TRY US**

Contact us for further information or for a trial order to see for yourself.

| Product                   | Thickness    | Width       | Length cutting | Coil | Protection Foil |
|---------------------------|--------------|-------------|----------------|------|-----------------|
| <b>DOBEL® / Laminated</b> |              |             |                |      |                 |
| Aluminum                  | 0,7 - 2,0 mm | Max 1250 mm | Max 4000 mm    | 3 T  | Yes             |



**Metalcolour A/S**  
 Agrovej 6  
 DK-4800 Nykøbing F.  
 Phone: +45 5484 9070  
 info@metalcolour.com

**Metalcolour Sverige AB**  
 Emaljervägen 7  
 SE-372 30 Ronneby  
 Phone: +46 457 781 00  
 info@metalcolour.com

**Metalcolour Asia Pte Ltd**  
 17 Tuas Avenue 4  
 SG-639368 Singapore  
 Phone: +65 6898 2535  
 info@metalcolour.com